

Radio controls

terra funk

The models FA5-K1P and FA5-K2P come with integrated tractor overturn protection as standard.



TERRA FA5-D1P

**5 YEARS
Warranty**



TERRA FA5-D2P



| Model | | TERRA FA5-D1P | TERRA FA5-D2P | TERRA FA5-K1P | TERRA FA5-K2P |
|---|------|-------------------|-------------------|-------------------|-------------------|
| Pull function | | ● | ● | ● | ● |
| Pulse or lasting | | ● | ● | ● | ● |
| Motor START/STOP | | ● | ● | ● | ● |
| Throttle regulation | | ● | ● | ● | ● |
| SMART 3in1 | | ● | ● | ● | ● |
| PTO switch on | | ● | ● | ● | ● |
| Emergency call - ARGUS -2 | | ● | ● | ● | ● |
| The tractor overturn protection (antikipp with el. throttle adjustment) | | / | / | ● | ● |
| Range (approx.) | m | 500 | 500 | 500 | 500 |
| Frequency | MHz | 433, 875-434, 650 | 433, 875-434, 650 | 433, 875-434, 650 | 433, 875-434, 650 |
| Number of functions | | 8 | 8 | 8 | 8 |
| Transmitter-dimensions / Weight | mm/g | 155x110x30 / 600 | 155x110x30 / 600 | 155x110x30 / 600 | 155x110x30 / 600 |
| Power source / batteries | mA | 600 | 600 | 600 | 600 |
| Receiver dimensions | mm | 200x120x75 | 200x120x75 | 200x120x75 | 200x120x75 |
| Operational voltage | V | 12 | 12 | 12 | 12 |
| Type of protection | | IP 65 | IP 65 | IP 65 | IP 65 |

● Standard | ● Option | / Not possible | D1P/K1P - single drum | D2P/K2P - double drum



Quick Charger SLG-250

- Intelligent charging technology
- Suitable for all FA-5 and FA7 models manufactured since 2000
- Operating voltage 12 V / 230 V



Tractor charger MLG-7/70-12 / 24

- EURO plug 12/24 V in motor vehicles
- Suitable for models FA-5



Tele Radio T-60-UF



Tele Radio T-70-1



Tele Radio T-80-1



Mechanical throttle regulation
For Terra Funk and Tele Radio.

| Model | | T60-UF | T70-1 | T80-1 |
|---------------------------------|------|-------------------|-------------------|-------------------|
| Suitable for | | Single drum winch | Single drum winch | Single drum winch |
| Pull function | | ● | ● | ● |
| Pulse or lasting | | ● | ● | ● |
| Motor START/STOP | | / | ● | ● |
| Throttle regulation | | ● | ● | ● |
| SMART 3in1 | | ● | ● | ● |
| Horn | | / | / | ● |
| Range (approx.) | m | 180 | 180 | 180 |
| Frequency | MHz | 2400 | 2400 | 2400 |
| Number of functions (max.) | | 6 | 8 | 8 |
| Transmitter-dimensions / Weight | mm/g | 113x66x35 / 140 | 185x80x44 / 400 | 170x117x40 / 640 |
| Power source / batteries | | 3 x 1,5 V AAA | 3 x 1,5 V AAA | 3,7 V Li-Ion |
| Receiver dimensions | mm | 133x120x45 | 190x160x75 | 120x116x50 |
| Operational voltage | V | 12-24 | 12-24 | 12-24 |
| Type of protection | | IP 65 | IP 65 | IP 65 |

● Standard | ● Option | / Not possible